

**LUBRICATING OIL COMPOSITION**

**Publication number:** JP2000336384

**Publication date:** 2000-12-05

**Inventor:** HASHIDA MIYUKI; HASHIMOTO TATSUYA

**Applicant:** NOK KULUVER KK

**Classification:**

- International: **C10M137/04; C10M129/74; C10M133/16; C10M137/10; C10N30/00; C10N40/02; C10M129/00; C10M133/00; C10M137/00; C10M137/00; (IPC1-7): C10M137/04; C10M129/74; C10M133/16; C10M137/10; C10N30/00; C10N40/02**

- European:

**Application number:** JP19990148042 19990527

**Priority number(s):** JP19990148042 19990527

**Report a data error here**

**Abstract of JP2000336384**

**PROBLEM TO BE SOLVED:** To obtain a lubricating oil composition capable of reducing the friction coefficient at an oil-impregnated bearing and improving abrasion resistance when the composition is used as the impregnation bearing oil. **SOLUTION:** This lubricating oil composition is obtained by compounding the base oil of a lubricating oil with (a) a phosphoric acid ester, (b) a fatty acid polyhydroxy alcohol ester, (c) triphenyl phosphorothionate and (d) an N- acyl-N-hydrocarboxyalkyl aspartic acid ester.

---

Data supplied from the **esp@cenet** database - Worldwide